



59.95 EUR

incl. 19% VAT, plus [shipping](#)

- M.2 NGFF !
- UMTS / 3G !
- LTE (EUROPE) !

Support:  [Specifications](#) | [Drivers \(Windows\)](#) | [Dialer Software](#)

The ME906E is a LTE module with NGFF interface , supporting LTE (FDD) B1/B2/B3/B5/B7/B8/B20,Penta-band DC-HSPA+/HSPA+/HSPA/WCDMA for Europe network coverage, low power consumption, Global Navigation Satellite System(GNSS), and European carrier certifications, enabling easier and more flexible design and integration into end devices. In addition, the ME906E supports NGFF features to optimize performance, power consumption, and usability.

ME906E is the ideal choice for Ultrabook, notebook, tablet etc.

Manufacturer	Huawei
Model	ME906E
Unlocked	Ready for use with global services. No contract required.
Network Bands	• LTE (FDD) B1/B2/B3/B5/B7/B8/B20 - Quad-band DC-HSPA+/HSPA+/HSPA/UMTS B1/B2/B4/B5/B8 - Quad-band EDGE/GPRS/GSM 1900/1800/900/850 MHz - GPRS/EDGE: Multi-slot Class 12 - WCDMA PS: UL (384 kbps)/ DL (384 kbps) - DC-HSPA+ :UL (5.76 Mbps)/ DL (42 Mbps) - LTE FDD: UL (50 Mbps)/ DL (100 Mbps) @Bandwidth 20M (CAT3) - Antenna interfaces x 2 - M.2 Socket 2
Data Speed	- USB 2.0 interface high speed - Power supply - UICC interface
Interface	Supply voltage range:3.135V~4.4V (3.3 V recommended)
Power Supply	Normal operation: -10°C to +55°C
Temp Range	Extended operation: -20°C to +70°C
GPS	Storage: -40°C to +85°C
Dimensions	GNSS: GPS Standalone, A-GPS, GPS XTRA, Glonass
	• 42x30x2.3 mm

Supported Systems

Windows 7/Windows 8/Android 4.0 or above

SIM Hotswap

IPV6

BodySAR

Special Features

Ultrabook feature support(ACT, WiFi Offload , DPTF)

Tunable Antenna

Supporting MO and MT

Supporting formats of PDU

Point-to-point and cell broadcast

Package Contents

New Huawei ME906E NGFF Embedded Module.