



999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- STC-24850 fan-controller

Support:  [Cables-Connectors](#)

#### 850W DC ATX P4 Power Supply (18-36VDC)

Now you can power every PC in your truck. 850W power and Pentium-4 connector are giving you all possibilities !  
The ATX connector has 24 pins. Along with the power supply there is a 24pol to 20pol ATX adapter included.

|                              |                                                      |
|------------------------------|------------------------------------------------------|
| Dimensions                   | 150mm[W] × 184mm[L] × 86mm[H] Standard ATX PS/2 size |
| Weight                       | 3.5 kgs                                              |
| Input Voltage Range          | 18 - 36VDC                                           |
| Output Power maximum         | 850W                                                 |
| Output Power maximum (rails) | +3.3V : 30A<br>+5.0V : 30A<br>+12.0V : 60A           |
| Remote sensing               | +5V and +3.3V                                        |
| Over Power Protection        | Load over 130%±10% of max. output power : shutdown   |
| Over Voltage Protection      | +5V, +12V & +3.3V Auto-recovery                      |
| Short Circuit Protection     | Main outputs shutdown and latch off                  |

|                             |                                                                   |
|-----------------------------|-------------------------------------------------------------------|
| Over Temperature Protection | OTP Level is set at 110°C                                         |
| Operating Temperature       | -20°C ~ +70°C                                                     |
| Storage Temperature         | -40°C~+80°C                                                       |
| Cooling                     | Build-in One 80x80x25mm Ball Bearing Fan with max. air flow 42CFM |

**Note :** Minimum power of 60W must be drawn at system startup time !