

539.00 EUR  
incl. 19% VAT, plus [shipping](#)



Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC is designed with 10-points Multi Capacitive Touch/Anti-Reflection Protection Glass type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Streamlined enclosure with narrow bezel design.

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC is designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel Panel PC.

- 8.0" 400 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Enclosed in robust aluminum casings
- A true Flat, easy-to-clean front surface with edge-to-edge design
- USB3.0 Support Lock Device
- Front IP65 for protection against water and dust
- 12V DC-input Support, with EOS, OVP design

|                   |                                                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display           | <ul style="list-style-type: none"> <li>– IP65, NEMA 4 rugged protection, metal front bezel</li> <li>– 8.0" With LED Backlight</li> <li>– 400 nits</li> <li>– 16.7M display color</li> <li>– 1024 x 768 @60Hz resolution</li> <li>– 160°/160° viewing angle (H/V)</li> <li>– 0.158 x 0.158mm pixel pitch</li> <li>– 4:3 aspect ratio</li> <li>– 700:1 contrast ratio</li> <li>– 30ms response time</li> </ul> |
| Touch Screen      | <ul style="list-style-type: none"> <li>– Projected capacitive type</li> <li>– 163.05 x 122.54mm ±0.2mm active range</li> <li>– Transparency ■ 85%</li> <li>– Operating force ■ 50g</li> <li>– Surface Hardness ■ 6H (JIS-5400)</li> <li>– Glass haze value■ 3%</li> </ul>                                                                                                                                    |
| Case              | <ul style="list-style-type: none"> <li>– Aluminum panel</li> <li>– Iron case</li> <li>– Silver + white color</li> <li>– Spray paint coating requirement</li> </ul>                                                                                                                                                                                                                                           |
| Main System       | <ul style="list-style-type: none"> <li>– Intel® Apollo Lake N3350 1.1GHz/DC processor</li> <li>– 1* DDR3L SO-DIMM (Max 8GB))</li> <li>– 128MB SPI Flash ROM</li> <li>– Watchdog Timer 256 levels, 0~255 sec.</li> <li>– OS Support Windows 10 / Linux</li> </ul>                                                                                                                                             |
| Storage           | <ul style="list-style-type: none"> <li>– 1* M.2 Socket (2242 size)</li> </ul>                                                                                                                                                                                                                                                                                                                                |
| Expansion         | <ul style="list-style-type: none"> <li>– 1* Mini PCIe for WIFI or 3G/4G</li> </ul>                                                                                                                                                                                                                                                                                                                           |
| I/O Connector     | <ul style="list-style-type: none"> <li>– 2* USB3.0</li> <li>– 1* RS232/422/485 + 1* RS232</li> <li>– 1* HDMI</li> <li>– 1* Realtek® RTL8111H GbE</li> <li>– 1* Locking Jack 12V DC input</li> <li>– 1* SIM card slot</li> <li>– 1* Power button</li> </ul>                                                                                                                                                   |
| Power Input       | <ul style="list-style-type: none"> <li>– AC version: 100~240V AC-DC 60W power adapter or</li> <li>– DC version: 12VDC with over current protection fuse</li> </ul>                                                                                                                                                                                                                                           |
| Power Consumption | <ul style="list-style-type: none"> <li>– 13W</li> </ul>                                                                                                                                                                                                                                                                                                                                                      |
| Dimensions        | <ul style="list-style-type: none"> <li>– 199.05 * 158.54 * 57.70mm</li> </ul>                                                                                                                                                                                                                                                                                                                                |
| Compliance        | <ul style="list-style-type: none"> <li>– CE, FCC, IP65(Front)-Option</li> </ul>                                                                                                                                                                                                                                                                                                                              |
| Safety            | <ul style="list-style-type: none"> <li>– Shock: 11ms duration</li> <li>– Vibration: 5~500Hz/1 Grms</li> </ul>                                                                                                                                                                                                                                                                                                |
| Temperature       | <ul style="list-style-type: none"> <li>– Operating: -10°C ~ 60°C</li> <li>– Storage: -20°C ~ 70°C</li> </ul>                                                                                                                                                                                                                                                                                                 |
| Warranty          | <ul style="list-style-type: none"> <li>– 2 Years Limited Warranty (Panel and Touch are only 1 Year Warranty)</li> </ul>                                                                                                                                                                                                                                                                                      |