


999.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Applied Solid Capacitor for CPU VRM to ensure a longer lifespan for system
- ECS Durathon Technology ensure the stability, reliability and performance of system.
- Dual Display design for multiple output support
- Integrated Printer (LPT) port / header to expand functionality
- Microsoft Windows 8 Certified
- Intel® VRD 12 Ready
- Supports DirectX® 11 to enhance graphical performance
- Supports HDMI 1.4a Technology ( resolution up to 1920X1200 ) and HDCP function
- Free Bundle: CyberLink Media Suite

Supports Intel® CNVi

|                       |                                                                                    |
|-----------------------|------------------------------------------------------------------------------------|
| <b>CPU</b>            | Onboard Intel® Bay Trail processors                                                |
|                       | On-Board CPU Intel® Bay Trail J1900 processor                                      |
|                       | VRD 12.0                                                                           |
|                       | Solid Capacitor for CPU side                                                       |
|                       | Supports Intel® Hyper-Threading Technology                                         |
| <b>GRAPHICS</b>       | Supports DirectX® 11                                                               |
|                       | Supports Full HD 1080P Blu-ray / HD-DVD Playback                                   |
|                       | Single-channel DDR3 Memory architecture                                            |
| <b>MEMORY</b>         | 1 X DDR3 SO-DIMM socket                                                            |
| <b>EXPANSION SLOT</b> | Support up to 8 GB                                                                 |
| <b>Storage</b>        | 1 X Mini PCI Express X1 slot(s) for Wi-Fi /Bluetooth modules                       |
|                       | 2 X Serial ATAIII 3Gb/s                                                            |
| <b>Audio</b>          | 6-Channel HD audio CODEC Realtek ALC662                                            |
|                       | Realtek ALC662 6-channel High Definition audio CODEC                               |
|                       | Meets performance requirements for Microsoft WLP 3.08 Vista premium and mobile PCs |
|                       | Six channel DAC supports 16/20/24-bit PCM format for 5.1 channel audio solution    |
|                       | Emulation of 26 sound environments to enhance gaming experience                    |
|                       | Voice Cancellation and Key Shifting in Karaoke mode                                |
|                       | Compatible with Direct Sound 3D™, A3D™, I3DL2                                      |
|                       | Realtek RTL8111G                                                                   |
|                       | Gigabit Fast Ethernet Controller                                                   |
|                       | 1 X USB3.1 Gen1 port(s) up to 5Gb/s                                                |
| <b>USB</b>            | 8 X USB2.0 port(s) Up to 480 Mb/s ( Back Panel 4 port(s), Onboard 4 port(s))       |

|                                 |                                                                                |
|---------------------------------|--------------------------------------------------------------------------------|
| <b>REAR PANEL I/O</b>           | 1 X PS/2 Keyboard & PS/2 mouse connectors                                      |
|                                 | 1 X Audio port (Line Out/Line In/Mic In)                                       |
|                                 | 1 X RJ-45 port                                                                 |
|                                 | 1 X HDMI port(s)                                                               |
|                                 | 1 X D-Sub (VGA) port(s)                                                        |
|                                 | 1 X USB3.1 Gen1 port(s)                                                        |
|                                 | 4 X USB2.0 port(s)                                                             |
|                                 | 1x DC-In connector                                                             |
|                                 | 1 X 4-pin CPU_FAN connector with smart fan                                     |
|                                 | 1 X 4-pin SYS_FAN connector with smart fan                                     |
|                                 | 1 X Front Panel MIC/Speaker out header                                         |
|                                 | 1 X Front Panel switch/LED header                                              |
|                                 | 1 X USB 2.0 header (Support additional 2 USB ports)                            |
|                                 | 2 X SATA II 3Gb/s connector(s)                                                 |
| <b>CONNECTORS &amp; HEADERS</b> | 1 X CLR_CMOS header                                                            |
|                                 | 2 X Serial port header (COM)                                                   |
|                                 | 1 X Parallel port header (LPT)                                                 |
|                                 | 1 X LVDS connector (optional)                                                  |
|                                 | AMI BIOS with 8 MB SPI Flash ROM                                               |
|                                 | Supports ACPI 5.0 & DMI                                                        |
|                                 | Dual Display Plug and Play, STR (S3) / STD (S4) , Hardware monitor, Multi Boot |
|                                 | Multi-Language BIOS                                                            |
|                                 | Audio, LAN, can be disabled in BIOS                                            |
|                                 | Dual-Monitor function                                                          |
|                                 | Mini ITX Form Factor                                                           |
|                                 | 170*170                                                                        |
|                                 | Windows 7 64-bit                                                               |
|                                 | Windows 8.1 32-bit                                                             |
| <b>OS Support</b>               | Windows 8.1 64-bit                                                             |
|                                 | Windows 10 64-bit                                                              |
|                                 | Windows 10 32-bit                                                              |
|                                 | CE/FCC Certification                                                           |
| <b>Certifications</b>           | ErP/EuP Certification                                                          |
|                                 | WHQL Certification                                                             |
|                                 | WHCK Certification                                                             |